

## LK-P12 Mobile Printer

- IP42 certified: dust and water protection
- Prints at 100mm (3.93 in) per second
- Large capacity for paper roll - up to 56mm (2.2 in)
- Adjustable paper width 12.7 – 58mm (.5 – 2.28 in)
- Flexible connectivity including PS-232C, USB, Bluetooth (iOS and standard), or Wi-Fi (802.11b/g/n)



The compact, rugged LK-P12 is designed to be your first choice when it comes to mobile printing. Its up to date, ergonomic design coupled with a 5 foot drop spec brings an ideal combination of strength and usability.

With impressive printing speeds and a high capacity battery, this 2 inch portable printer delivers fast, powerful printing for a range of applications.



The LK-P12 from Informs comes with all the accessories you need to start using your printer the day it arrives, including a battery, belt clip, AC charging cable, and USB communication cable. With a two year warranty and an unbeatable price, the LK-P12 is the best value on the market.

Discover the LK-P12: the perfect addition to your mobile workforce

<b>Print Mechanism</b>		Direct thermal 2" label & receipt
<b>Media Type</b>		Receipt, Label
<b>Media Width</b>		12.7-58mm (.5-2.28 in)
<b>Media Size</b>		56mm (2.2 in) OD
<b>Media Length/No Peel Mode</b>		2.7-300/19-300mm (.11-11.81/.75 -11.81 in)
<b>Resolution</b>		203 DPI
<b>Print Width</b>		48mm (1.89 in)
<b>Fonts</b>		Font A, Font B, Download bitmap and true type font
<b>Barcode Symbols</b>	<b>1D</b>	UPC-A, UPC-E, EAN-8, EAN-13, EAN-128, RSS, Postnet, CODE39, CODE93, CODE128, TF, CODABAR
	<b>2D</b>	PDF417, QR Code, Maxicode, GS-1, Data-matrix, Aztec
<b>Interface</b>	<b>Standard</b>	RS-232 (mini DIN connector), USB
	<b>Option</b>	Bluetooth, Wi-Fi, iOS
<b>Driver</b>		Windows (2000, XP, Vista, 7, 10), Symbian OS Windows mobile (Pocket PC, 2003, 6x), Android, Windows CE 4.2/5.0/6.0, Linux, Blackberry
<b>Emulation</b>		EXC/POS, ZPL, CPCL, Command compatible
<b>Sensor</b>		Gap, Black mark, Paper end, Peeler
<b>Battery</b>		Hard pack 7.4V 2600mAh
<b>Method of Charge Battery</b>		AC/DC charger
<b>Impact Resistance</b>		1.5M (4.92 in) standard
<b>Environment Data</b>	<b>Operating</b>	-10-50°C (14-122°F)/10-90% RH
	<b>Storage</b>	-20-60°C (-4-140°F)/10-90% RH
<b>Dimensions (WxDxH)</b>		100x158x85mm (3.94x6.22x3.35 in)
<b>Weight</b>		580g (20.46 oz) with battery